

COMPLETE SEIKOH GIKEN, CO. LTD. POLISHING FIXTURE LIST

Polishing Fixture SFP-550 - I.P.C. Type

Part Number	Description
PH55-FLM-16	Ferrule/PC - 1.25mm diam - Std Flange - Flat Face - Zirconia - MU/LC - 16 Axis - I.P.C. type
PH55-FLM-40	Ferrule/PC - 1.25mm diam - Std Flange - Flat Face - Zirconia - MU/LC - 40 Axis - I.P.C. type
PH55-FF-20	Ferrule/PC - 2.5mm diam - Std Flange - PreDome - Zirconia - 20 Axis - I.P.C. type
PH55-FF-24	Ferrule/PC - 2.5mm diam - Std Flange - PreDome - Zirconia - 24 Axis - I.P.C. type
PH55-FF-40	Ferrule/PC - 2.5mm diam - Std Flange - PreDome - Zirconia - 40 Axis - I.P.C. type
PH55-FF-48	Ferrule/PC - 2.5mm diam - Std Flange - PreDome - Zirconia - 40 Axis - I.P.C. type
PH55-F0391-440	Ferrule/PC - Custom 2.5mm ferruleHolder - 20 Axis - I.P.C. Type (OFS Termini)
PH55-F0332-800	Ferrule/PC - Custom 2.0mm ferruleHolder - 24 Axis - I.P.C. Type (Lemo F2)
PH55-F0423-210	Univ. MIL PC ferruleHolder for D1.0 to D2.5mm ferrule, 24-axis
PH55-F0423-210A	Univ. MIL PC ferruleHolder for D1.0 to D2.5mm ferrule, 24-axis, with CMH
PH55-F0423-210B	Univ. MIL PC ferruleHolder for D1.0 to D2.5mm ferrule, 24-axis, with Setting jig
PH55-F0423-210C	Univ. MIL PC ferruleHolder for D1.0 to D2.5mm ferrule, 24-axis, with CMH and Setting jig
PH55-FF8A-18-1.5	Ferrule/APC - 2.5mm diam - 1.5mm Flange - Step Ferrule, 18 axis - I.P.C. type
PH55-FF8A-18-1.3	Ferrule/APC - 2.5mm diam - 1.3mm Flange - Step Ferrule, 18 axis - I.P.C. type
PH55-FF8C-18-1.5	Ferrule/APC - 2.5mm diam - 1.5mm Flange - Conical Ferrule, 18 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FF8C-18-1.3	Ferrule/APC - 2.5mm diam - 1.3mm Flange - Conical Ferrule, 18 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FF8A-40-1.5	Ferrule/APC - 2.5mm diam - 1.5mm Flange - Step Ferrule, 40 axis - I.P.C. type
PH55-FF8A-40-1.3	Ferrule/APC - 2.5mm diam - 1.3mm Flange - Step Ferrule, 40 axis - I.P.C. type
PH55-FF8C-40-1.5	Ferrule/APC - 2.5mm diam - 1.5mm Flange - Conical Ferrule, 40 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FF8C-40-1.3	Ferrule/APC - 2.5mm diam - 1.3mm Flange - Conical Ferrule, 40 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FP-20	FC/PC Fixture, 20 axis - I.P.C. type
PH55-FP8R-18-I	FC/APC Step Fixture - Narrow Key 2mm - 18 axis - I.P.C. type
PH55-FP8R-24	FC/APC Step Fixture - Narrow Key 2mm - 24 axis - I.P.C. type
PH55-FP8N-18-I	FC/APC Step Fixture - Wide Key 2.14mm - 18 axis - I.P.C. type
PH55-FP8N-24	FC/APC Step Fixture - Wide Key 2.14mm - 24 axis - I.P.C. type
PH55-FP8RC-18-I (PH55-FP8RC-18)	FC/APC Conical Fixture - Narrow Key 2mm - 18 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FP8RC-24	FC/APC Conical Fixture - Narrow Key 2mm - 24 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FP8NC-18-I (PH55-FP8NC-18)	FC/APC Conical Fixture - Wide Key 2.14mm - 18 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-FP8NC-24	FC/APC Conical Fixture - Wide Key 2.14mm - 24 axis - I.P.C. type (30&35 degree chamfer angle)
PH55-CP-20	SC/PC Fixture, 20 axis - I.P.C. type
PH55-CP-32	SC/PC Fixture, 32 axis - I.P.C. type
PH55-CP-48	SC/PC Fixture, 48 axis, IPC type. (Requires Eccentric Drive & Support Plates 1 ea.)
PH55-CP-32FX	SC/PC Fixture, Fixed Type, DPC Mode, Linear Config., 32-Axis
PH55-CP8A-18	SC/APC - Step Ferrule - Fixture, 18 axis - I.P.C. type
PH55-CP8A-24	SC/APC - Step Ferrule - Fixture, 24 axis - I.P.C. type
PH55-CP8A-32	SC/APC - Step Ferrule - Fixture, 32 axis - I.P.C. type
PH55-CP8C-18	SC/APC - Conical Ferrule - Fixture, 18 axis - I.P.C. type (35 degree chamfer angle)
PH55-CP8C-24	SC/APC - Conical Ferrule - Fixture, 24 axis - I.P.C. type (35 degree chamfer angle)
PH55-CP8C-32	SC/APC - Conical Ferrule - Fixture, 32 axis - I.P.C. type (35 degree chamfer angle)
PH55-CP8C-48	SC/APC, Conical Fixture, 48 axis. (Requires Eccentric Drive & Support Plates 1 ea.)
PH55-CP8C-16FX	SC/APC CONICAL, 16 AXIS, FIXED DPC TYPE, FOR RIGID CABLE (Fixing connector from rear side with shoulder screw)
PH55-CP8C-32FX	SC/APC - Conical Ferrule - Fixture, 32 axis - Fixed Type, DPC Mode
PH55-SP-20	ST/PC Fixture, 20 axis - I.P.C. type
PH55-SP-28	ST/PC Fixture, 28 axis - I.P.C. type
PH55-PL-24	LC/PC Fixture, 24 axis - I.P.C. type (LC Secure Compatible/ Not Duplex compatible)
PH55-PL-40	LC/PC Fixture, 40 axis - IPC type (LC Secure Compatible/ Not Duplex compatible)
PH55-PL-48	LC/PC Fixture, 48 axis - IPC type (Duplex Compatible)
PH55-PL-32DHP	LC/PC, Simplex and Duplex, 32 axis - High Pressure Type
PH55-PL-48DHP	LC/PC, Simplex and Duplex, 48 axis - High Pressure Type
PH55-PL-72DHP	LC/PC Fixture, 72 Axis, 36 connectors for Duplex High Pressure. (Requires Eccentric Drive & Support Plates 1 ea.)
PH55-PL-32DFX	LC/PC, Duplex Fixture, 32 axis - Fixed type for SFP-560A (Not available for 550C series)
PH55-PL-48DFX	LC/PC, Duplex Fixture, 48 axis - Fixed type for SFP-560A (Not available for 550C series)
PH55-PL8A-20-B	LC/APC Fixture, 20 axis - I.P.C. type
PH55-PL8A-24	LC/APC Fixture, 24 axis - I.P.C. type
PH55-PL8A-40	LC/APC Fixture, 40 axis - I.P.C. type
PH55-PL8A-48	LC/APC Fixture, 48 axis - I.P.C. type
PH55-PL8A-24HP	LC/APC Fixture, 24 axis - I.P.C. type (High Pressure Type)
PH55-PL8A-40HP	LC/APC Fixture, 40 axis - I.P.C. type (High Pressure Type)
PH55-PL8A-48HP	LC/APC Fixture, 48 axis - I.P.C. type (High Pressure Type)
PH55-PL8A-54HP	LC/APC Fixture, 54 axis - I.P.C. type (High Pressure Type)
PH55-PL8A-66HP	LC/APC Fixture, 66 axis, Simplex. (Requires Eccentric Drive & Support Plates 1 ea.)
PH55-PL8A-32DHP-POR	LC/APC, Duplex Fixture, 32 axis (for SG uniboot LC/APC duplex connector ONLY!)
PH55-PL8A-32DFX-POR	LC/APC, 32 Axis, Duplex for Intellicross Uniboot Only; Polarity Rotate, Fixed DPC Pressure
PH55-PL8A-24FX	LC/APC, 24 FIXED DPC type (Simplex only)
RP55C-08A	Eccentric Drive plate including knock pin for ultra axis fixture for SFP-550C
RP56A-10A	Eccentric Drive plate including knock pin for ultra axis fixture for SFP-560A Series
RP55S3-08A	Eccentric Drive plate including knock pin for ultra axis fixture for SFP-550E3/550S3
RP55C-05A	Eccentric Support plate including knock pin for ultra axis fixture for SFP-550C/550E3/550S3
RP56A-07A	Eccentric Support plate including knock pin for ultra axis fixture for SFP-560A Series
PH55-PM-24	MU/PC Fixture, 24 axis - I.P.C. type
PH55-PM-40	MU/PC Fixture, 40 axis - I.P.C. type
PH55-PM8A-20	MU/APC Fixture, 20 axis - I.P.C. type
PH55-M5P-18	SMA905 Fixture, 18 axis Fixed type
PH55-M5P-20	SMA905 Fixture, 20 axis I.P.C. type

PH55-M6P-12	SMA906 Fixture, 12 axis
PH55-M6P-18	SMA906 Fixture, 18 axis
PH55-F0262-910	LX.5 APCHolder, 12 Axis
PH55-F0262-150	LX.5 APCHolder, 12 Axis (new)
PH55-F0332-540	ITT 1.25mm ML FerruleHolder, 16 axis- I.P.C. type w/ Stopper
PH55-EF-18-HS	E2000 Ferrule/PC I.P.C. Fixture, for Hubner & Suhner, 18 axis
PH55-EF-24-H	E2000 Ferrule/PC I.P.C. Fixture, for Hubner & Suhner, 24 axis
PH55-EF-40-H	E2000 Ferrule/PC I.P.C. Fixture, for Hubner & Suhner, 40 axis
PH55-EF8A-18-H	E2000 Ferrule/APC I.P.C. Fixture, for Hubner & Suhner, 18 axis
PH55-EF8A-24-H	E2000 Ferrule/APC I.P.C. Fixture, for Hubner & Suhner, 24 axis
PH55-EF8A-40-H	E2000 Ferrule/APC I.P.C. Fixture, for Hubner & Suhner, 40 axis
PH55-EF-18-RS	E2000 Ferrule/PC I.P.C. Fixture, for Reichle & De-Massari, 18 axis
PH55-EF-24-R	E2000 Ferrule/PC I.P.C. Fixture, for Reichle & De-Massari, 24 axis
PH55-EF-40-R	E2000 Ferrule/PC I.P.C. Fixture, for Reichle & De-Massari, 40 axis
PH55-EF8A-18-R	E2000 Ferrule/APC I.P.C. Fixture, for Reichle & De-Massari, 18 axis
PH55-EF8A-24-R	E2000 Ferrule/APC I.P.C. Fixture, for Reichle & De-Massari, 24 axis
PH55-EF8A-40-R	E2000 Ferrule/APC I.P.C. Fixture, for Reichle & De-Massari, 40 axis
PH55-EP8A-24A	E2000/APC PLUG, Fixture, H&S, Fixed, 24 axis
PH55-EP8A-20-I	E2000/APC PLUG, IPC, 20 axis
PH55-OPT8*9	OptiTap I.P.C. Fixture, includes 10 pcs. IPC-X-SCH Housing, 9 axis
PH55-OPT8*12	OptiTap I.P.C. Fixture, includes 13 pcs. IPC-X-SCH Housing, 12 axis
PH55-OPT8*20	OptiTap I.P.C. Fixture, No IPC-X-SCH Housing Required, 20 axis
PH55-OPT8C-18FX	OptiTap Fixture, Snap-in, Fixed Type, 18-axis. (accepts Fast and Slim Connect)
PH55-OPT8C-24FX	OptiTap Fixture, Fixed type, 24-axis
PH55-F0420-910	Holder for CS and SN ferrule, 24-axis (12 duplex fibers), IPC spring type w/cable mgmtHolder (CMH) including wide handles
PH55-F0420-900	Holder for CS and SN ferrule, 64-axis (32 duplex fibers), IPC spring type w/cable mgmtHolder (CMH) including wide handles
PH55-F0420-900B	IPC holder for CS and SN ferrule, 64-ferrules (32 two-fiber-cables), Plate spring type IPC, with CMH, Circular layout
PH55-F0423-700	Holder for CS and SN ferrule, IP-16, BTW / PC ferrule, Plate spring IPC, with CMH, Circular layout (48-axis)
PH55-F0423-700FX	Fixed DPC holder for SN, CS, IP-16, BTW / PC ferrule, Linear slide stopper, with CMH, Circular layout
PH55-F0423-740	IPC holder for MDC(LC) / PC ferrule, 48-ferrules (6 ferrules per side x 8 sides), Plate spring type IPC, with CMH, Circular layout
PH55-F0423-740FX	Fixed DPC holder for MDC(LC) / PC ferrule, 48-ferrules (6 ferrules per side x 8 sides), Linear-slide fixation, with CMH, Circular layout
PH55-F0423-930	IPC holder for CS and SN / APC ferrule, 24-ferrules (6 ferrules per side x 4 sides), Plate spring type IPC, with CMH, Circular layout
PH55-F0423-930FX	Fixed DPC holder for CS and SN / APC ferrule, 24-ferrules (6 ferrules per side x 4 sides), Linear-slide fixation, with CMH, Circular layout
PH55-F0423-940	IPC holder for CS and SN / APC ferrule, 48-ferrules (12 ferrules per side x 4 sides), Plate spring type IPC, with CMH, Circular layout
PH55-F0423-940FX	Fixed DPC holder for CS and SN / APC ferrule, 48-ferrules (12 ferrules per side x 4 sides), Linear-slide fixation, with CMH, Circular layout
PH55-CS-20	IPC Holder for CS/PC, 20 connectors/40 ferrules, Snap-in type, Circular layout
PH55-CS-20FX	Fixed DPC Holder for CS/PC, 20 connectors/40 ferrules, Snap-in type, Circular layout for 560A2 Polisher Series
PH55-CS8A-18	IPC Holder for CS/APC, 18 connectors/36 ferrules, Snap-in type IPC, Circular layout
PH55-CS8A-18FX	Fixed DPC Holder for CS/APC, 18 axis/36 ferrules), Snap-in type, Circular layout
PH55-MDC-24	IPC Holder MDC/PC, 24 connectors/48 ferrules, snap-in type, circular layout
PH55-MDC-24FX	Fixed DPC Holder MDC/PC, 24 connectors/48 ferrules, snap-in type, circular layout
PH55-MDC8A-24	IPC Holder MDC/APC, 24 connectors/48 ferrules, snap-in type, circular layout
PH55-MDC8A-24FX	Fixed DPC Holder MDC/APC, 24 connectors/48 ferrules, snap-in type, circular layout
PH55-MDCJR-24	IPC Holder for MDC JR, 24 axis/48 ferrules, plate spring type, linear layout
PH55-MDCJR-24FX	Fixed DPC Holder, MDC JR, PC, 24 connectors/48 ferrules, linear slide and layout
PH55-MDCJR8A-24	MDC-JR/APCHolder, 24 connectors/48 ferrules/IPC Spring Type
PH55-MDCJR8A-24FX	Fixed DPC, MDC-JR/APCHolder, 24 connectors/48 ferrules
PH55-SN-24	SN/PC Connector Holder, 24 connectors/48 ferrules, IPC, snap-in, circular layout
PH55-SN-24FX	Fixed DPC Holder, SN/PC, 24 connectors/48 ferrules, Snap-in, Circular Layout
PH55-SN8A-24	SN/APC Holder, 24 connectors/48 ferrules, Snap-in, Circular Layout, IPC Type
PH55-SN8A-24FX	Fixed DPC Holder, SN/APC, 24 connectors/48 ferrules, Snap-in, Circular Layout
PH55-SNJR-12	SN JR, PC Holder, 12 connectors/24 ferrules, Snap-in, Metal Adapters, Circular Layout, IPC Type
PH55-SNJR-12FX	Fixed DPC, SN JR, PCHolder, 12 connectors/24 ferrules, Snap-in, Metal Adapters, Circular Layout
PH55-SNJR-24	SN JR, PC Holder, 24 connectors/48 ferrules, Snap-in, Metal Adapters, Circular Layout, IPC Type
PH55-SNJR-24FX	Fixed DPC, SN JR, PC Holder, 24 connectors/48 ferrules, Snap-in, Metal Adapters, Circular Layout
PH55-SNJR8A-12	SN JR APC, 12 axis/24 ferrules, snap in type, metal adapters circular layout, IPC
PH55-SNJR8A-12FX	Fixed DPC SN JR APC, 12 connectors/24 ferrules, snap in type, metal adapters circular layout
PH55-SNJR8A-24	IPC Holder SN JR, APC 24 connectors/48 ferrules, snap-in type, metal adapters circular layout
PH55-SNJR8A-24FX	Fixed DPC Holder SN JR, APC 24 connectors/48 ferrules, snap-in, metal adapters, circular layout
PH55-SNCOM-12	SN-COMPACT / PC plug, '12-plugs (24 ferrules), Snap-in type IPC, Metal adapter, Circular layout
PH55-SNCOM-12FX	SN-COMPACT / PC plug, '12-plugs (24 ferrules), Snap-in type, Fixed (DPC), Metal adapter, Circular layout
PH55-SNCOM-24	SN-COMPACT / PC plug, '24-plugs (48 ferrules), Snap-in type IPC, Metal adapter, Circular layout
PH55-SNCOM-24FX	SN-COMPACT / PC plug, '24-plugs (48 ferrules), Snap-in type, Fixed (DPC), Metal adapter, Circular layout
PH55-SNCOM8A-12	SN-COMPACT / APC plug, '12-plugs (24 ferrules), Snap-in type IPC, Metal adapter, Circular layout
PH55-SNCOM8A-12FX	SN-COMPACT / APC plug, '12-plugs (24 ferrules), Snap-in type, Fixed (DPC), Metal adapter, Circular layout
PH55-SNCOM8A-24	SN-COMPACT / APC plug, '24-plugs (48 ferrules), Snap-in type IPC, Metal adapter, Circular layout
PH55-SNCOM8A-24FX	SN-COMPACT / APC plug, '24-plugs (48 ferrules), Snap-in type, Fixed (DPC), Metal adapter, Circular layout

Polishing Fixture SFP-550/560A2 - MT Polishing

Part Number	Description
PH55-MT-12S1	MT/PC Fixture, 12 axis (1mm Protrusion Type, NOT One Lever)
PH55-MT-24S1	MT/PC Fixture, 24 axis (1mm Protrusion Type, NOT One Lever)
PH55-MT8A-12S1	MT/APC Fixture, 12 axis (1mm Protrusion Type, NOT One Lever)
PH55-MT8A-24S1	MT/APC Fixture, 24 axis (1mm Protrusion Type, NOT One Lever)
PH55-MT-12R1	MT/PC 12-axis RepolishingHolder (1mm Protrusion Type, NOT One Lever)
PH55-MT8A-12R1	MT/APC 12-axis Repolishing Holder (1mm Protrusion Type, NOT One Lever)
PH55-MT-12SQ1-B	MT/PC Fixture, 12 Axis, One-lever action (comes with economy type wide handle)
PH55-MT-24SQ1-B	MT/PC Fixture, 24 Axis, One-lever action (comes with economy type wide handle)
PH55-MT8A-12SQ1-B	MT/APC Fixture, 12 Axis, One-lever action (comes with economy type wide handle)
PH55-MT8A-24SQ1-B	MT/APC Fixture, 24 axis, One-lever action (comes with economy type wide handle)
PH55-MT-32SQ1-B	MT/PC Fixture, 32 axis, One Lever MT action, comes with wide handles
PH55-MT8A-32SQ1-B	MT/APC Fixture, 32 axis, One Lever MT action, comes with wide handles
PH55-MT8A-12QD	MT/APC, 12 axis Fixture, Standard sized MT Ferrule, One Lever action, 4.4mm epoxy window
PH55-MT8A-24QD	MT/APC, 24 axis Fixture, Standard sized MT Ferrule, One Lever action, 4.4mm epoxy window
PH55-MTRJ-12S	MT/PC Fixture, 12 axis, One-body type with torque wrench
PH55-MTRJ-24S	MT/PC Fixture, 24 axis, One-body type with torque wrench
PH55-TMT8A-12Q	TMT/APC, 12 axis Fixture, Standard sized TMT Ferrule, One Lever action, 4.4mm epoxy window
PH55-TMT8A-24Q	TMT/APC, 24 axis Fixture, Standard sized TMT Ferrule, One Lever action, 4.4mm epoxy window
PH55-MT-PRM-B1	MT/MPO Pressure Module for 550C/550E3/550S3 (Rotary pressure adjuster) (Z-axis free type)
PH55-MT-PRM-B2	MT/MPO Pressure Module for 550E/ 550S/550S2 (Rotary pressure adjuster) (Z-axis free type)
PH55-MT-PRM-B3	MT/MPO Pressure Module for 120A/550/550B (Rotary pressure adjuster) (Z-axis free type)